

»POWRBANK MAX

EMISSION-FREE, SILENT POWER

The POWRBANK MAX reduces CO2 emissions and eliminates unwanted noise. The POWRBANK MAX can handle large loads including, but not limited to, tower cranes, pumps, and hoists. It can handle both the peak loads at engine start-up, as well as the low loads. The power generator is only used to recharge the POWRBANK battery.

With the onboard energy control module, the POWRBANK constantly monitors load levels and automatically switches between generator power and stored energy.

- Eliminates generator oversizing
- Minimizes generator emissions
- Conserves fuel
- Provides extended periods of silent power
- Reduces generator service frequency



MODEL	VOLTS	kW	kWh	PHASE
M250.250/480	480	250	250	3

POWER

Output (stand alone)	Standing Rating 1 min (kW)	375
	Standing Rating 10 min (kW)	312.5
	Standing Rating 60 min (kW)	275
	Output Rating Prime (kW)	225
	Maximum Load (Single Phase Operation)	166kW for 7 minutes
Combined System Output	Continuous Pass Through Per Phase (A)	301
	Maximum Combined Output Per Phase (A)	301
	Run-Time @ Max Combined Output (H)	Unlimited
Input/Output	AC Input Voltage Range	440V – 520V
	AC Output Voltage - 60 Hz	480V
	Input Connections	480V BusBar and 400A Camlock
	Output Connections	480V BusBar and 400A Camlock
	Protection	Overload, Overheat, Short Circuit, Earth Fault, Back Feed Protection

STORAGE

Type	LFP
Nominal Capacity @ 25°C	272 kWh
Charge Time @ 25°C ¹	3 Hr
System Efficiency	95%
Battery Management System	Industrial Grade Intelligent Passive BMS Optimized for HES
Expected Cycle Life (To 80% Depth of Discharge)	>5000 Cycles
Maintenance Charge Cycle	3 Months

CONTROL

Control Panel	ECM 7" Touch Screen Control Module
Temperature Control	HVAC System w/ Thermostat
Remote Generator Start	Dry Contact Relay
Remote Communication	3G/4G Dual SIM Modem/Router, POWR2 Portal

ENVIRONMENTAL

Water/Ingress Protection Rating	Nema 3R/ IP55
Operating Temperature Range (°C)	10 – 40°C
Sound Level (dBA)	

MECHANICAL

Dimensions L x W x H	8ft x 10ft x 8.5ft
Weight (lbs)	17,338 lbs
Lift Points	Forklift Pockets, Lifting Rings

¹Charge time dependent on available power of external source and operating temperature

This document was updated in November 2022. While POWR2 aims to ensure all documentation is accurate, no responsibility will be accepted for errors or omissions. POWR2 maintains a policy of continuous product innovation and reserves the right to change specifications without notice. Information on product data sheets may change, as well as legislation, and you are strongly advised to keep up to date with recently issued regulations, standards and guidelines. This document is not intended to be contractual.